

Commercial Water Solutions



COMMERCIAL WATER SOFTENERS

- ◆ Four methods to initiate regeneration; meter immediate or delayed, time delayed or pressure differential
- ◆ Fully adjustable cycle sequencing controller
- ◆ Electronic microprocessor tracks system water usage daily and automatically adjusts to meet demand



United Water offers a large line-up of heavy-duty water filtration & treatment options that are designed for commercial and industrial applications. We are here to help you find the best systems for your needs. In addition to our standard available products we also offer expert custom design to ensure you install the perfect system tailored specifically to your needs.

Single, Duplex & Triplex System Configuration Progressive Flow Options



Choosing the correct system can be a complex task and we are here to help provide you with the information you need to make the right choice for any commercial and industrial application. Call 877-414-7873

Model Number	Pipe Size	Grain Capacity		Flow Rate (gpm) ¹		Tank Sizes		Mineral Quantity (cu/ft)	Salt Capacity (lbs)	Back-wash Rate
		Max @ 15lbs per cu/ft	Max @ 6lbs per cu/ft	Cont. @ 15psi Drop	Peak @ 25psi Drop	Mineral Tank	Brine Tank			
AT90-954SM	1.5"	90,000	60,000	33	42	14 x 65	18 x 40	3.0	340	4.2
AT120-954SM	1.5"	120,000	80,000	36	50	16 x 65	18 x 40	4.0	590	5.3
AT150-954SM	1.5"	150,000	100,000	40	57	18 x 65	24 x 50	5.0	900	7.0
AT180-954SM	1.5"	180,000	120,000	44	60	21 x 62*	24 x 50	6.0	900	10.0
AT210-954SM	1.5"	210,000	180,000	43	58	21 x 62*	24 x 50	7.0	900	10.0
AT300-954SM	1.5"	300,000	200,000	45	60	24 x 72*	30 x 50	10.0	1200	12.0
AT90-956SM	2"	90,000	60,000	39	50	14 x 65	18 x 40	3.0	340	4.2
AT120-956SM	2"	120,000	80,000	47	60	16 x 65	18 x 40	4.0	590	5.3
AT150-956SM	2"	150,000	100,000	53	69	18 x 65	24 x 50	5.0	900	7.0
AT180-956SM	2"	180,000	120,000	70	91	21 x 62*	24 x 50	6.0	900	10.0
AT210-964SM	2"	210,000	180,000	66	85	21 x 62*	24 x 50	7.0	900	10.0
AT300-956SM	2"	300,000	200,000	73	94	24 x 72*	30 x 50	10.0	1200	12.0
AT450-956SM	2"	450,000	300,000	84	109	30 x 72*	39 x 48	15.0	1510	20.0
AT600-956SM	2"	600,000	400,000	93	119	36 x 72*	39 x 60	20.0	1870	30.0
AT750-956SM	2"	750,000	500,000	98	127	42 x 72*	39 x 60	25.0	1660	35.0
AT900-956SM	2"	900,000	600,000	95	123	42 x 72*	42 x 60	30.0	1930	35.0
AT1050-956SM	2"	1,050,000	700,000	100	129	48 x 72*	42 x 60	35.0	1750	45.0
AT1200-956SM	2"	1,200,000	800,000	98	127	48 x 72*	50 x 60	40.0	2730	45.0
AT300-959SM	3"	300,000	200,000	98	126	24 x 72*	30 x 50	10.0	1200	12.0
AT450-959SM	3"	450,000	300,000	144	186	30 x 72*	39 x 48	15.0	1510	20.0
AT600-959SM	3"	600,000	400,000	172	222	36 x 72*	39 x 60	20.0	1870	30.0
AT750-959SM	3"	750,000	500,000	190	244	42 x 72*	39 x 60	25.0	1660	35.0
AT900-959SM	3"	900,000	600,000	176	265	42 x 72*	42 x 60	30.0	1930	35.0
AT1050-956SM	3"	1,050,000	700,000	194	251	48 x 72*	42 x 60	35.0	1750	45.0
AT1200-956SM	3"	1,200,000	800,000	98	127	48 x 72*	50 x 60	40.0	2730	45.0

Custom configurations available, please contact us for details.

Notes: 1 - Quality of water may vary depending upon flow rate and water conditions.

* These systems are also available using the following tanks: Steel non-code pressure vessels - Fiberglass ASME code pressure vessels - Steel ASME code pressure vessels.