



MADE IN USA

Commercial Carbon Backwash

Features

- *Four Solid state microprocessor*
- *Fully adjustable cycle sequencing controller*
- *Stores system configuration and date*
- *Coin cell lithium battery back-up with 24 hour carry over*



Single, Duplex & Triplex System
Configuration
Progressive Flow Options



1.5" & 2" Control Valve



3" Control Valve



Specifications

Aquatek Carbon Filters - 1.5" Commercial

Model Number	ATCBF-5.0-1.5-C	ATCBF-7.0-1.5-C	ATCBF-10.0-1.5-C	ATCBF-15.0-1.5-C
Cubic Ft. Media	5	7	10	15
Flow Rate 5-10 gpm/ft ²	10 - 20 gpm	12 - 25 gpm	15 - 30 gpm	35 - 70 gpm
Continues Flow Rate*	10 gpm	12 gpm	15 gpm	35 gpm
Backwash Rate	17	25	48	70
Connection Size	1.5"	1.5"	1.5"	1.5"
Water Pressure Limit	40 - 100 psi	40 - 100 psi	40 - 100 psi	40 - 100 psi
Electrical	120 v. 60 Hz	120 v. 60 Hz	120 v. 60 Hz	120 v. 60 Hz
Mineral Tank Diameter	16"	21"	24"	30"
Mineral Tank Height	65"	62"	72"	72"
Approx. Shipping Weight	300 lbs.	400 lbs.	600 lbs.	825 lbs.

Aquatek Carbon Filters - 2.0" Commercial

Model Number	ATCBF-5.0-2.0-C	ATCBF-7.0-2.0-C	ATCBF-10.0-2.0-C	ATCBF-15.0-2.0-C
Cubic Ft. Media	5	7	10	15
Flow Rate 5-10 gpm/ft ²	10 - 20 gpm	12 - 25 gpm	15 - 30 gpm	35 - 70 gpm
Continues Flow Rate*	10 gpm	12 gpm	15 gpm	35 gpm
Backwash Rate	17	25	48	70
Connection Size	2.0"	2.0"	2.0"	2.0"
Water Pressure Limit	40 - 100 psi	40 - 100 psi	40 - 100 psi	40 - 100 psi
Electrical	120 v. 60 Hz	120 v. 60 Hz	120 v. 60 Hz	120 v. 60 Hz
Mineral Tank Diameter	16"	21"	24"	30"
Mineral Tank Height	65"	62"	72"	72"
Approx. Shipping Weight	300 lbs.	400 lbs.	600 lbs.	825 lbs.

NOTE* - Continues flow rate should not exceed 1 hour run time

